

# INCINER8

## Waste Incineration Model A2600(HF)

### Multipurpose Incinerator

We can now offer our range of incinerators exclusively throughout Europe and the rest of the world through our dealer network. Our range of units are fully CE certified, ensuring that we meet the highest standards in safety and construction.

### Large Capacity Unit Model A2600(HF)

The Model A2600 is a proven and unique design which is currently operating in many different applications throughout the world. They are unique in build quality, durability and ease of installation, operation and servicing.

They are many variants including medical waste, animal waste, camp waste and general waste applications.



### INCINER8 For a Cleaner Environment



Model A2600(HF) Flow Diagram

### Ease of Use

- Auto ignition.
- No pilots to light.
- Automatic control and temperature monitoring
- Built-in skid facilitates placement

### Fuel Efficiency

- Rapid incineration means low fuel consumption.
- Higher burn rate than other models.
- Up to 500kgs per hour (dependant on application).
- Thick refractory lining rated to 1600 deg C in main chamber retains heat, increasing efficiency.

### Quality Built to Last

- Heat resistant 5mm steel.
- Stainless steel stack.
- 12cm of refractory lining — steel reinforced

## KEY FEATURES

- Low running and maintenance costs
- Fully Automatic and simple to operate control panel
- Afterburner Preheat
- Incineration Temperatures in Excess of 1300 degrees C
- 5mm Steel Casing and Fully insulated
- Dense Refractory Concrete Lining Rated to 1600 degrees C
- Solid Hearth to Allow Maximum Burnout
- Large Top Opening Lid For Easy Loading
- Wide Door For Ash Removal
- Stainless Steel Flue as standard
- After Burner Fitted as standard
- 12 Month or 1000 hours Warranty.
- Optional Stainless Steel Casing
- Optional gas cleaning systems
- Custom sizes available with up to 500kgs per hour
- CE Marking
- Heat Recovery System option



Self Contained Units

### Technical Specifications

### Model A2600(HF)

Fuel	Oil
Capacity (Cubic Mtr)	1.92
Ave Capacity	1200kg
Fuel Consumption (ltrs / hr)	10

### External Dimensions

Length (mm)	3110
Width (mm)	2150
Height Incl. Flue (mm)	4250
Door Opening (mm)	1000 x 2000

### Internal Dimensions

Length (mm)	2200
Width (mm)	1050
Height Incl. Flue (mm)	800

### Operation

Min. Operating Temperature	950
Max. Operating Temperature	1320
Residency Time in Second Chamber	2 secs.
Temperature Monitoring	YES



### Dealer Stamp

### INCINER8

INCINER8 House. Balmoral Drive,  
Southport PR9 8PZ, England  
Tel +44 (0) 1704 506506  
Fax +44 (0) 1704506666  
Email : [info@inciner8.com](mailto:info@inciner8.com)  
Web : [www.inciner8.com](http://www.inciner8.com)