

MODEL	CAPACITY (m ³)	BURN RATES (kg per hour*)			DIMENSIONS (in meters)			DOOR SIZE (in meters)	WEIGHT (in KG)	SECONDARY CHAMBER (afterburn)	GAS RETENTION (seconds)	FUEL USAGE (litres)
		Animal	General	Medical	Length	Width	Height					
Sirocco	0.2	-	15	-	1.00	0.80	1.64	0.57 Ø	70	✗	-	-
I8-10	0.1	-	15	-	0.73	0.46	1.93	0.33 x 0.33	400	✗	-	3 - 4 ltrs p/h
I8-10S	0.1	15	20	13	0.73	0.46	3.28	0.33 x 0.33	500	✓	0.5	3 - 4 ltrs p/h
I8-20	0.18	-	20	-	1.07	0.66	2.61	0.49 x 0.49	700	✗	-	4 - 6 ltrs p/h
I8-20S	0.18	-	35	-	1.07	0.66	3.58	0.49 x 0.49	800	✓	0.5	4 - 6 ltrs p/h
I8-20A/G	0.18	30	35	15	1.07	0.66	4.31	0.49 x 0.49	1230	✓	2	7 - 9 ltrs p/h
I8-40	0.36	-	45	-	1.24	0.92	3.29	0.56 x 0.56	920	✗	-	8 - 10 ltrs p/h
I8-40S	0.36	-	45	-	1.24	0.92	3.93	0.56 x 0.56	1250	✓	0.5	8 - 10 ltrs p/h
I8-40A/G	0.36	40	45	20	1.24	0.92	4.40	0.56 x 0.56	1520	✓	2	9 - 11 ltrs p/h
I8-55	0.54	-	65	-	1.52	0.92	3.60	0.72 x 0.83	1500	✗	-	10 - 12 ltrs p/h
I8-55S	0.54	-	65	-	1.52	0.92	4.02	0.72 x 0.83	1670	✓	0.5	10 - 12 ltrs p/h
I8-55A/G	0.54	60	65	30	1.52	0.92	4.48	0.72 x 0.83	2100	✓	2	10 - 13 ltrs p/h
I8-75	0.75	-	70	-	1.61	1.19	3.62	0.99 x 0.91	2200	✗	-	10 - 14 ltrs p/h
I8-75S	0.75	-	70	-	1.61	1.19	4.03	0.99 x 0.91	2150	✓	0.5	10 - 14 ltrs p/h
I8-75A/G	0.75	65	70	35	1.61	1.19	4.68	0.99 x 0.91	2450	✓	2	10 - 15 ltrs p/h
I8-140A/G	1.35	120	150	60	2.54	1.10	4.18	1.45 x 0.75	3100	✓	2	14 - 19 ltrs p/h
I8-200A/G/M	1.92	200	250	150	3.07	1.37	4.39	2.04 x 1.06	5000	✓	2	20 - 25 ltrs p/h
I8-250A/G/M	2.40	300	380	250	3.59	1.39	4.64	2.53 x 1.06	8000	✓	2	25 - 30 ltrs p/h
I8-700A/G/M	6.75	800	900	600	6.04	1.91	5.75	4.58 x 1.50	15000	✓	2	40 - 50 ltrs p/h
I8-1000A/G/M	8.70	900	1000	700	6.54	1.84	5.37	4.00 x 1.50	21500	✓	2	40 - 50 ltrs p/h

2018 - ENHANCED MEDICAL RANGE - All feature additional safety features, high powered ID fans and stainless steel exterior shell as standard.

I8-M15	0.13	-	-	25	0.75	0.75	2.72	0.50 x 0.31	652	✓	0.5	4 - 5 ltrs p/h
I8-M20	0.18	-	-	30	1.07	0.66	4.31	0.49 x 0.49	1230	✓	2	7 - 9 ltrs p/h
I8-M40	0.36	-	-	35	1.24	0.92	4.40	0.56 x 0.56	1520	✓	2	9 - 11 ltrs p/h
I8-M50	0.54	-	-	40	1.52	0.92	4.48	0.72 x 0.83	2100	✓	2	10 - 13 ltrs p/h
I8-M70	0.75	-	-	45	1.61	1.19	4.68	0.99 x 0.91	2450	✓	2	10 - 15 ltrs p/h
I8-M80	0.57	-	-	65	2.08	1.10	3.84	0.55 Ø	2500	✓	2	15 - 20 ltrs p/h
I8-M100	1.35	-	-	70	2.54	1.10	4.18	1.45 x 0.75	3100	✓	2	14 - 19 ltrs p/h
I8-M120	1.25	-	-	120	1.85	1.11	8.10	0.64 x 0.54	6000	✓	2	13 - 18 ltrs p/h